

QCR-ARS6-900

Artarm系列



技术参数 Technical Parameter

功能 Function	打磨、上下料、3C Polishing,Material handling,3C products	
轴数 Total axis	6	
负载 Payload	6kg	
重复定位精度 Position repeat accuracy	± 0.03mm	
最大单轴 速度 Max speed	1轴 axis1(底部旋转)	337.5° /sec
	2轴 axis2(大臂)	270° /sec
	3轴 axis3(小臂)	375° /sec
	4轴 axis4(手臂旋转)	300° /sec
	5轴 axis5(手臂摆动)	375° /sec
	6轴 axis6(手臂旋回)	468° /sec
各轴运动 范围 Max operating area	1轴 axis1(底部旋转)	± 170°
	2轴 axis2(大臂)	+100° -/135°
	3轴 axis3(小臂)	+110° -/155°
	4轴 axis4(手臂旋转)	± 170°
	5轴 axis5(手臂摆动)	± 120°
	6轴 axis6(手臂旋回)	± 360°
工作温度 Working temperature	0~+45℃	
安装方式 Installation parameters	地面支架安装 Floor mounted	
本体重量 Robot weight	60Kg	
能耗 Power consumption	2.2kw	
最大臂展 Maximum reach	915mm	
防护等级 IP Grade	IP54/IP65	

工作范围 Working Range

